

REC'D PCT/PTO 05 OCT 2004  
PCAU 02 / 00774

#2

12 JUL 2002

PA 857012

# THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

June 20, 2002

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 10/120,350

FILING DATE: April 12, 2002

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

By Authority of the  
COMMISSIONER OF PATENTS AND TRADEMARKS



*N. Woodson*  
N. WOODSON  
Certifying Officer

BEST AVAILABLE COPY

3C923 U.S. PTO

Please type a plus sign (+) inside this box ☒   
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO/SB/05 (08-00)   
 Approved for use through 10/31/2002. OMB 0651-0032   
 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

# UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. YU183US   
 First Inventor KIA SILVERBROOK   
 Title The Processing of Images for High Volume   
 Pagewidth Printing   
 Express Mail Label No.

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)   
 (Submit an original and a duplicate for fee processing)
2. ☒ Applicant claims small entity status.   
 See 37 CFR 1.27.
3. ☒ Specification [Total Pages 26]   
 (preferred arrangement set forth below)
  - Descriptive title of the invention
  - Cross Reference to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to sequence listing, a table, or a computer program listing appendix
  - Background of the invention
  - Brief Summary of the invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 14]
5. Oath or Declaration [Total Pages 3]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63 (d))   
 (for continuation/divisional with Box 17 completed)
  - c. ☐ DELETION OF INVENTOR(S)   
 Signed statement attached deleting inventor(s)   
 named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO: Assistant Commissioner for Patents   
 Box Patent Application   
 Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Form (CRF)
  - b. Specification Sequence Listing on:
    - i. ☐ CD-ROM or CD-R (2 copies); or
    - ii. ☐ paper
  - c. ☐ Statements verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

9. ☒ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☐ Power of Attorney
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
13. ☐ Preliminary Amendment
14. ☐ Return Receipt Postcard (MPEP 503)   
 (Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)   
 (if foreign priority is claimed)
16. ☐ Other: .....

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP)

of prior application No.: 09,112,767

Prior application information:

Examiner An H Do

Group / Art Unit: 2853

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

## 18. CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label



or ☐ Correspondence address below

Name KIA SILVERBROOK   
 Address 393 Darling Street,   
 City Balmain State NSW Zip Code 2041   
 Country Australia Telephone +61-2-9818-6633 Fax +61-2-9819-6711

Name (Print/Type) KIA SILVERBROOK Registration No. (Attorney/Agent)   
 Signature [Signature] Date April 8, 2002

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

# FEE TRANSMITTAL for FY 2002

Patent fees are subject to annual revision.

☒ Applicant claims small entity status. See 37 CFR 1.27

TOTAL AMOUNT OF PAYMENT (\$410)

## Complete if Known

Application Number  
 Filing Date  
 First Named Inventor Kia Silverbrook  
 Examiner Name  
 Group Art Unit  
 Attorney Docket No. YU183US

## METHOD OF PAYMENT (check all that apply)

☒ Check ☐ Credit card ☐ Money Order ☐ Other ☐ None

☐ Deposit Account:

Deposit Account Number  
 Deposit Account Name

The Commissioner is authorized to: (check all that apply)

☐ Charge fee(s) indicated below ☐ Credit any overpayments  
☐ Charge any additional fee(s) during the pendency of this application  
☐ Charge fee(s) indicated below, except for the filing fee to the above-identified deposit account.

## FEE CALCULATION

### 1. BASIC FILING FEE

Large Entity		Small Entity		Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)		
101	740	201	370	Utility filing fee	370
108	330	208	165	Design filing fee	
107	510	207	255	Plant filing fee	
108	740	208	370	Reissue filing fee	
114	160	214	80	Provisional filing fee	

SUBTOTAL (1) (\$) 370

### 2. EXTRA CLAIM FEES FOR UTILITY AND REISSUE

Total Claims	Extra Claims	Fee from below	Fee Paid
18	-20** =	9	0
3	-3** =	42	0
Multiple Dependent			

Large Entity		Small Entity		Fee Description
Fee Code	Fee (\$)	Fee Code	Fee (\$)	
103	18	203	9	Claims in excess of 20
102	84	202	42	Independent claims in excess of 3
104	280	204	140	Multiple dependent claim, if not paid
109	84	209	42	** Reissue independent claims over original patent
110	18	210	9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$) 0

\*\*or number previously paid, if greater; For Reissues, see above

## FEE CALCULATION (continued)

### 3. ADDITIONAL FEES

Large Entity/Small Entity

Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for ex parte reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
116	110	216	55	Extension for reply within first month	
116	400	216	200	Extension for reply within second month	
117	920	217	460	Extension for reply within third month	
118	1,440	218	720	Extension for reply within fourth month	
128	1,860	228	980	Extension for reply within fifth month	
119	320	219	160	Notice of Appeal	
120	320	220	160	Filing a brief in support of an appeal	
121	280	221	140	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,280	241	640	Petition to revive - unintentional	
142	1,280	242	640	Utility issue fee (or reissue)	
143	460	243	230	Design issue fee	
144	620	244	310	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Processing fee under 37 CFR 1.17(q)	
126	180	126	180	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	40
146	740	246	370	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	740	249	370	For each additional invention to be examined (37 CFR § 1.129(b))	
179	740	279	370	Request for Continued Examination (RCE)	
169	900	169	900	Request for expedited examination of a design application	

Other fee (specify)

\*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 40

## SUBMITTED BY

Name (Print/Type) Kia Silverbrook  
 Signature

Registration No.  
 (Attorney/Agent)

## Complete (if applicable)

Telephone +61-2-9818-6633  
 Date April 8, 2002

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

This is a C-I-P of USSN 09/112,767 filed on July 10, 1998

# **TITLE OF THE INVENTION**

**THE PROCESSING OF IMAGES FOR HIGH VOLUME PAGEWIDTH PRINTING**

## **INVENTOR**

Kia Silverbrook

## **STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT**

Not Applicable

## **FIELD OF THE INVENTION**

This invention relates to the processing of images for high volume pagewidth printing. More particularly, this invention relates to a method of processing an image for printing, an image processing apparatus and an inkjet printer.

## **REFERENCED PATENT APPLICATIONS**

This application is a continuation-in-part application of United States Application Number 09/112,767. The following United States applications and patents are hereby incorporated by reference:

6,227,652	6,213,588	6,213,589	6,231,163	6,247,795
09/113,099	6,244,691	6,257,704	09/112,778	6,220,694
6,257,705	6,247,794	6,234,610	6,247,793	6,264,306
6,241,342	6,247,792	6,264,307	6,254,220	6,234,611
09/112,808	09/112,809	6,239,821	09/113,083	6,247,796
09/113,122	09/112,793	09/112,794	09/113,128	09/113,127
6,227,653	6,234,609	6,238,040	6,188,415	6,227,654
6,209,989	6,247,791	09/112,764	6,217,153	09/112,767
6,243,113	09/112,807	6,247,790	6,260,953	6,267,469
09/425,419	09/425,418	09/425,194	09/425,193	09/422,892
09/422,806	09/425,420	09/422,893	09/693,703	09/693,706
09/693,313	09/693,279	09/693,727	09/693,708	09/575,141
09/113,053,	09/526,504			

## BACKGROUND OF THE INVENTION

High volume, high resolution printing is an objective that has been sought by the manufacturers of wide format printers for some time. Wide format printers have been available to the public for many years. Examples of popular wide format printers are the Hewlett Packard (HP) 1000/5000, the HP 3000/3500, the Epson 7000/10 000 and many others.

These printers all have a traversing printhead that traverses a print medium while depositing ink on the medium. Applicant believes that these printers suffer from inherent disadvantages, particularly when attempts are made to utilize the design of such printers in order to achieve faster printing speeds at high resolutions.

Central to the problem of achieving high printing speeds is the ability to achieve a printhead that is capable of generating the necessary number of ink dots at a suitable rate. Further, in order to achieve accurate printing, it is desirable that a row or band of the image be created in as little print cycles as possible, and preferably in a single print cycle. It follows that it is undesirable for a traversing printhead to be used in an attempt to achieve high print speeds and that a single printhead incorporating a suitable number of inkjet nozzles is required.

Thermal printheads also referred to as bubble jet printheads and piezoelectric printheads have been available for some time. These suffer from excessive heat build up and energy consumption and have therefore been found by the applicant to not be suitable for use in a pagewidth configuration. A number of disadvantages associated with such printheads are set out in US application no 09/526,504.

The applicant has developed a printhead chip that is capable of producing images having a resolution as high as 1600 dpi. These chips are manufactured using integrated circuit fabrication techniques. Details of the chips are provided in the above referenced applications and patents. Applicant believes that these printhead chips are extremely suitable for use in wide format printers. The reason for this is that such chips operate at extremely high speeds due to the large number of nozzle arrangements required in a single chip and due to the fact that such chips can be driven at an extremely high cyclical rate.

The Applicant has been faced with a number of difficulties in order to achieve the effective use of such printhead chips in wide format printers. One particular difficulty identified by the Applicant is the effective control of a number of such printhead chips to

achieve accurate printing. This control must incorporate the use of effective image processing tools that are capable of processing stored images at a rate that corresponds with the physical rate of printing achievable by a number of the above printhead chips.

## SUMMARY OF THE INVENTION

According to a first aspect of the invention, there is provided a method of processing an image for printing, the method comprising the steps of:

receiving image data in an image storage format;

transforming the image data into print data at a rate of at least one billion pixels per second; and

communicating the print data to a printhead.

According to a second aspect of the invention, there is provided an image processing apparatus for a printer, the image processing apparatus comprising

a data input means that is configured to receive image data in an image storage format;

a data processing means that is operatively connected to the data input means and is configured to process the image data at a rate of at least one billion pixels per second to transform the data into print data; and

a data communication means that is operatively connected to the data processing means and is configured to communicate the print data to a printhead.

According to a third aspect of the invention, there is provided an inkjet printer that comprises

a support structure;

a platen positioned in the support structure;

a print assembly positioned operatively with respect to the platen to define a printing zone between the platen and the print assembly, the print assembly comprising

an elongate carrier; and

a number of printhead chips positioned on the carrier, the printhead chips together defining a printhead;

an image processing apparatus that is operatively arranged with respect to the print assembly, the image processing apparatus comprising

a data input means configured to receive image data in an image storage format;

a data processing means that is configured to process the image data at a rate of at least one billion pixels per second to transform the data into print data; and

a data communication means that is configured to communicate the print data to the printhead; and

a feed mechanism positioned on the support structure for feeding a print medium through the printing zone.

The invention is now described, by way of example, with reference to the accompanying drawings. The following description is not intended to limit the broad scope of the above summary.

## BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings,

Figure 1 shows a schematic, three-dimensional view of part of a printing mechanism of a print assembly incorporating an image processing apparatus, in accordance with the invention, of a printer, also in accordance with the invention;

Figure 2 shows a front view of the printing mechanism of Figure 1;

Figure 3 shows a rear view of the printing mechanism of Figure 1;

Figure 4 shows a three dimensional, external view of the printer;

Figure 5 shows a schematic, three-dimensional view of operative parts of the printer;

Figure 6 shows a schematic, exploded view of the printer;

Figure 7 shows a schematic, side sectioned view of a portion of the printer incorporating the print assembly;

Figure 8 shows an exploded view of an operative portion of the printing mechanism;

Figure 9 shows a cross sectional view of an operative portion of the printing mechanism;

Figure 10 shows a high-level block diagram of the image processing apparatus;

Figure 11 shows an expanded block diagram of a page expansion unit of the image processing apparatus;

Figure 12 shows a block diagram of the image processing apparatus incorporating the page expansion unit;

Figure 13 shows a schematic, three-dimensional view of part of a printhead chip of the print assembly of the printer, showing one nozzle arrangement of the printhead chip; and

Figure 14 shows a schematic, three-dimensional view of a printhead module that incorporates a printhead chip.

## DETAILED DESCRIPTION OF THE INVENTION

In Figure 4, reference numeral 10 generally indicates a printer, in accordance with the invention.

10 The printer 10 has a support structure 12 that supports a print assembly 14 above a substrate. The support structure 12 includes a pair of spaced feet 16 and a leg 18 extending from each foot 16. The print assembly 14 is mounted on the legs 18 to span the legs 18.

A media tray 20 is positioned between the legs 18. The media tray 20 is configured to store suitable print media, such as paper 22.

The paper 22 is fed from a media feed mechanism in the form of a media roll 166 through the print assembly 14 and on to a take up spool 24. An electronics enclosure 26 is also positioned between the legs 18 to enclose various electronic components that are described below.

20 The print assembly 14 includes a lid 28, with a handle 30, and a front cover 32. The lid 28 and front cover 32 are positioned between a pair of end moldings 34.

The print assembly 14 also includes a color TFT LCD 36 with touch screen navigation. A stop button 38 is also provided to enable a user to stop operation of the print assembly 14.

The print assembly 14 and its various components are shown in further detail in the remaining Figures.

30 In Figures 1 to 3, reference numeral 40 generally indicates a printing mechanism of the print assembly 14. As can be seen in the drawings, the printing mechanism 40 is segmented. In particular, the printing mechanism 40 includes an image processing apparatus, in accordance with the invention, that includes nine printed circuit boards (PCB's) 42 connected to each other with corresponding connector blocks 44.

The printing mechanism 40 further includes a printhead 41 having seventy-two printhead modules 46. Each PCB 42 is configured to control eight printhead modules 46. It



follows that nine PCB's 42 are provided. The printhead modules 46 are described in further detail below.

Each PCB 42 includes a print engine controller (PEC) 48. The PEC's 48 are also described in further detail below.

Each PCB 42 also includes a memory storage device in the form of memory chips and more particularly in the form of 64 Mbit external DRAM chips 50. The DRAM chips 50 cooperate with the PEC 48 in a manner that is described below.

Further, each PCB 42 includes a quality authentication (QA) chip 52. Details of a suitable QA chip are set out in the above referenced United States application no.

10 09/113,053 and are therefore not set out in this description. The QA chip 52 serves to inhibit unauthorized refilling of ink in the manner described in 09/113,053, in addition to other functions such as ensuring the quality of print media used with the printer 10.

An endmost PCB 42 includes a serial connector 54 that permits serial data cables 56 to be connected to the PCB's 42.

Each PCB 42 is connected to its associated printhead modules 46 with a flexible PCB 58.

20 The printing mechanism 40 includes a metal chassis 60 that extends between a pair of side moldings 61 that are positioned in the end moldings 34. The PCB's 42 are mounted on the chassis 60. The chassis 60 has a generally U-shaped cross section. A channel 62 of an Invar alloy is positioned on the chassis 60.

A chassis molding 64 of a plastics material is positioned on an outside of the chassis 60 and the channel 62. Each PCB 42 is mounted on the chassis molding 64.

The chassis molding 64 defines a pair of recesses 66 on an outer side of the chassis molding 64. The recesses 66 extend a length of the chassis molding 64. A busbar 68 is positioned in each recess 66. The busbars 68 are configured to supply electrical power to the PCB's 42.

30 An ink reservoir assembly 70 is positioned in the Invar channel 62. The ink reservoir assembly 70 includes an ink distribution arrangement 72. Each printhead module 46 is positioned on a respective ink distribution arrangement 72. In particular, each printhead module 46 is removably mounted on its ink distribution arrangement 72 to facilitate removal and replacement when necessary.

The ink reservoir assembly 70 includes a plurality of ink reservoir moldings 76. Each ink reservoir molding 76 corresponds with an associated printhead module 46. The

ink reservoir moldings 76 are positioned end-to-end along and within the Invar channel 62. Each ink reservoir molding 76 defines a plurality of elongate ink channels 74, each accommodating a differently colored ink. Thus, effective elongate ink channels extend a length of the Invar channel 62.

10 An end cap molding 78 is positioned on an endmost ink reservoir molding 76. The end cap molding 78 has a plurality of connectors 80 defined thereon and in alignment with respective ink channels 74 when the end cap molding 78 is positioned on said endmost ink reservoir molding 76. The connectors 80 are connectable to an ink hose connector 82. The ink hose connector 82 is, in turn, connected to each of a plurality of ink hoses 84. It follows  
that each hose 84 is in fluid communication with a respective ink channel 74. Each hose 84 supplies the ink reservoir assembly 70 with ink of a particular color. For example, the hoses 84 can carry Cyan (C), Magenta (M), Yellow (Y) and Black (K) inks, respectively. In this case, four hoses 84 are provided. Also, each reservoir molding 76 defines four ink channels 74. Alternatively, the hoses 84 can carry Cyan (C), Magenta (M), Yellow (Y), Red (R), Green (G) and Blue (B) inks, respectively. In this case, six hoses 84 are provided. Also, each reservoir molding 76 then defines six ink channels 74. Instead of six differently colored inks, the six hoses 84 can carry CMYK and Infrared (IR) inks and a fixative (F) for high speed printing so that the inks can dry rapidly.

20 Each hose 84 is connected to a respective ink container 86 (Figure 5), so that each hose 84 is connected between an ink container 86 and a particular ink channel 74. The hoses 84 are connected to their respective containers 86 with T-piece connectors 94 shown in Figure 1.

The print assembly 14 includes a plurality of capping devices 88 that correspond with respective printhead modules 46. Each capping device 88 is displaceable between an operative position in which it serves to cap its respective printhead module 46, to inhibit drying of ink, and an inoperative position in which ink can be ejected from the printhead module 46. A camshaft 90 is positioned in the chassis 60. A translating member 92 interconnects the camshaft 90 and the capping devices 88, so that rotational movement of the camshaft 90 results in reciprocal movement of the capping devices 88 between their  
30 operative and inoperative positions.

The camshaft 90 is driven with a suitable motor, indicated generally at 96 in Figure 5.

Further detail of the print assembly 14 is shown in Figure 7. As can be seen in this drawing, the front cover 32, the lid 28 and a rear cover 98 together define a housing 100 for the print assembly 14.

A plurality of ink cartridges 102 is positioned beneath the lid 28. Each ink cartridge 102 stores one of the inks mentioned above. Each ink cartridge 102 is positioned between a pair of clips 104 so that it can be replaced when necessary. Each ink cartridge 102 and a respective ink reservoir 86 are in fluid communication with each other, when the ink cartridge 102 is received between the clips 104.

A pair of platens, in the form of an upper platen 106 and a lower platen 108 is positioned within the housing 100. A pair of spaced primary rollers in the form of an upper primary roller 110 and a lower primary roller 112 is provided to displace the paper 22 through the print assembly 14. The upper roller 110 is positioned at an upper end of the platens 106, 108, while the lower roller 112 is positioned between the platens 106, 108. The rollers 110, 112 are configured to drive a sheet of the paper 22 over, consecutively, an inner surface of the lower platen 108 and an outer surface of the upper platen 106. Thus, the paper 22 passes over the upper roller 110, while the lower roller 112 is positioned between upwardly and downwardly moving portions of the paper 22.

A brush 114 is pivotally mounted at 116 to the housing 100. The brush 114 has an arcuate transverse profile that corresponds with the upper primary roller 110. The brush 114 is positioned in the housing 100 so that the paper 22 can pass between the brush 114 and the housing 100.

A pinch roller 118 is positioned downstream of the brush 114 to bear against the upper primary roller 110. Thus, when the paper 22 is displaced from between the brush 114 and the upper primary roller 110, the pinch roller 118 retains the paper 22 against lateral movement.

The upper platen 106 defines an upper printing zone 120 and a lower cutting zone 122. A gap 124 is defined between the upper and lower printing zones 120, 122. A plurality of spiked wheels 126 is partially received through the gap 124 to engage the paper 22 and the lower primary roller 112. A crossbar 128 is operatively positioned with respect to the spiked wheels 126 to retain the spiked wheels 126 in position. The spiked wheels 126 and the pinch roller 118 are configured so that a suitable tension is set up in the paper 22 when the paper 22 passes over the printing zone 120 of the upper platen 106.

The chassis 60 and channel 62 are positioned above the printing zone 120 of the upper platen 106. The chassis 60 and the channel 62 are connected to a displacement mechanism 129 so that the chassis 60 and channel 62 can be displaced from the printing zone 120 when necessary. In particular, the chassis 60 and channel 62 are displaceable between an operative position in which the printhead modules 46 are a distance from the printing zone 120 that is suitable for printing and an inoperative position in which the paper 22 can be released from the printing zone 120.

10 The chassis 60 and channel 62 are connected to the pinch roller 118 with suitable metalwork 130. Further, the chassis 60 and channel 62 are connected to the crossbar 128. It follows that, when the displacement mechanism 129 is operated, the pinch roller 118 and the spiked wheels 126 are displaced from the upper platen 106 together with the chassis 60 and the channel 62.

The displacement mechanism 129 includes a camshaft 132 and a pusher 134. The pusher 134 is connected to the chassis 60 and the channel 62 so that, upon rotation of the camshaft 132, the chassis 60 and channel 62 are displaced towards and away from the printing zone of the upper platen 106.

Upper idler rollers 136 are rotatably mounted above the upper platen 106 so that the paper 22 is received between the upper platen 106 and the upper idler rollers 136.

20 A lower, sprung idler roller 138 is mounted on the lower platen 108 to be partially received through a gap 140 defined in the lower platen 108. The sprung idler roller 138 is configured and positioned to bear against the lower primary roller 112. Thus, an upwardly moving portion of the paper 22 is gripped, and passes between, the lower primary roller 112 and the sprung idler roller 138.

The print assembly 14 includes a cutting mechanism 142 that is mounted in the housing 100 above the cutting zone 122 of the upper platen 106. The cutting mechanism includes a cutter 146 that traverses the paper 22 to cut the paper 22. The cutting mechanism 142 includes an optical sensor 144 so that the cutter 146 can be stopped when it reaches an end of a cutting stroke. The cutting zone 122 defines a cutting formation 148 that cooperates with the cutter 146 to facilitate cutting of the paper 22.

30 As can be seen in Figure 6, the print assembly 14 includes an air impeller 150 and a motor 152 to drive the air impeller 150. The air impeller 150 serves to generate an air current within the housing 100 for cooling purposes. An air filter 153 is also positioned in the housing 100 to filter the air passing through the housing 100. The air impeller 150 also

serves to generate the air current to a sufficient extent to minimize the build up of dust on the printhead modules 46.

As can further be seen in Figure 6, the primary rollers 110, 112 are connected to a gearbox 154 that is mounted on a bracket 156. The gearbox 154 and bracket 156 are positioned on one of the legs 18 and covered with one of the end moldings 34. Thus, the primary rollers 110, 112 serve to drive the paper 22 through the print assembly 14.

A printhead bracket 157 is positioned in the housing 100 and extends between the legs 18. The printhead bracket 157 provides a support structure for the chassis 60 and channel 62. The printhead bracket 157 also provides a support structure for the upper idler rollers 136.

The housing 100 is shaped to define an opening 158 for passage of the paper 22 into and out of the print assembly 14. Feed rollers 162 are rotatably mounted on a tie bar 160 that extends between the legs 18. The feed rollers 162 are positioned so that the paper 22 passes over the feed rollers 162 when the paper is fed into the print assembly 14. The tie bar 160 also serves a structural purpose in that it provides structural rigidity to the printer 10.

Discharge rollers 164 are rotatably mounted on the upper platen 106. The discharge rollers 164 are positioned so that the paper 22 passes over the discharge rollers 164 when the paper 22 is fed from the print assembly 14.

Both the media roll 166 and the take up spool 24 are driven with a media roll drive motor 168 and a take up spool drive motor 170, respectively (Figure 5).

The printer 10 includes a power supply unit 172 that is positioned in the electronics enclosure 26. The power supply unit 172 is configured to be powered by either a 110V or 220V power supply. Further, the power supply unit 172 is configured so that up to 90Amps can be drawn from the power supply unit 172. The power supply unit 172 is connected with power cables 173 to various components of the printer 10, such as the various drive motors to supply the components with required operational energy.

The printer 10 includes an ATX motherboard 174 that is also positioned in the electronics enclosure 26. A printhead interface card 176 is mounted on the motherboard 174. The printhead interface card 176 is connected to the nine PCB's 42 with suitable data cables 178. Thus, conventional print data supplied to the interface card 176 from the motherboard 174 can be converted into a suitable form for reading by the various PCB's 42.

The printer 10 includes a hard drive unit 180. Conveniently, the hard drive unit 180 can have a capacity of 40 Gigabytes. This facilitates the storage of entire images to be printed. The hard drive unit 180 is connected to the motherboard 174 in a conventional fashion. The hard drive unit 180 is a conventional hard drive unit and is therefore capable of storing images in any number of formats, such as the well-known JPEG format. The manner in which the image data is read from the hard drive unit 180 is also conventional. As is set out below, printing of the images is digitally controlled as a result of the printhead technology utilized in this invention. It follows that transferal of image data from the hard drive unit 180 to the PCB's 42, via the printhead interface card 176 can take place without the requirement of significant data transformation, in particular, without the requirement of digital to analogue signal conversion.

The interface card 176 is also connected to a motor and LCD controller PCB 182 to control operation of the various drive motors and the TFT LCD. Details of such control are set out in the above referenced applications and are therefore not provided in this description. The motor and LCD controller PCB 182 is connected to a cut off switch 184 that is, in turn, connected to the stop button 38 so that operation of the printer 10 can be halted.

As can be seen in Figure 14, the printhead modules 46 each include a printhead chip 186. The printhead chip 186 can be in the form of any of the printhead chips described in the above referenced applications/patents. Each printhead module 46 includes a carrier 187 in which the printhead chip 186 is positioned. The carrier 187 defines a suitable connection zone for the flexible PCB 58 associated with the printhead chip 186. Figure 13 shows a schematic diagram of part of a printhead chip 186 that is suitable for use in the printer 10. Each printhead module 46 includes what are known as on chip fiducials 258. The on chip fiducials 258 are essentially in the form of markers to facilitate accurate alignment of the printhead modules 46 in the print assembly 14.

The printhead chip 186 is described in detail in the above referenced US application no. 09/112,767 and will therefore not be described in such detail in this specification. Briefly, however, the chip 186 includes a wafer substrate 188. A CMOS drive circuitry layer 190 is positioned on the wafer substrate 188 and is connected to the flexible PCB 58.

A plurality of nozzle arrangements 210 is positioned on the CMOS drive circuitry layer 190. For the purposes of convenience, one such nozzle arrangement 210 is shown in Figure 13. The printhead chip 186 comprises a multiple replication of the nozzle

arrangement 210 on the wafer substrate 188. As set out in the above referenced applications and patents, the printhead chip 186 is the product of an integrated circuit fabrication technique. Replication of components in order to achieve a product is a well-known feature of such a fabrication technique. It follows that the printhead chip 186 can readily be understood by a person of ordinary skill in the field of chip fabrication.

Each nozzle arrangement 210 includes a thermal bend actuator 192 that is positioned on the CMOS layer 190 to receive an actuating signal from the CMOS layer 190. In particular, the thermal bend actuator 192 includes a support post 194 that is mounted on the CMOS layer 190 to extend from the CMOS layer 190. The thermal bend actuator 192 includes an actuator arm 196 that is fixed to, and extends from, the support post 194. The actuator arm 196 includes a heating layer 198 in the form of an electrical heating circuit of a material having a coefficient of thermal expansion that is such that the material is capable of performing useful work on a MEMS scale as a result of expansion upon heating. The heating layer 198 is positioned on a layer 200 of a material having a coefficient of thermal expansion that is less than that of the heating layer 198 defining the electrical heating circuit. The heating layer 198 is positioned intermediate the layer 200 and the substrate 188 so that the actuator arm 196 is bent away from the substrate 188 when a current is passed through the heating layer 198.

Nozzle chamber walls 202 are positioned on the CMOS layer 190. A roof wall 204 is positioned on the nozzle chamber walls 202. The nozzle chamber walls 202 and the roof wall 204 define a nozzle chamber 206. The roof wall 204 defines an ink ejection port 208 from which ink is ejected, in use.

A paddle member 212 is mounted on the actuator arm 196 to extend into the nozzle chamber 206. The paddle member 212 is configured and positioned in the nozzle chamber 206 so that, upon displacement of the actuator arm 196, as described above, ink is ejected from the nozzle chamber 206.

The actuator arm 196 is connected to the CMOS layer 190 through the support post 194 so that the heating layer 198 can receive an electrical signal from the CMOS layer 190.

As can be seen in Figures 3 and 9, the printhead chips 186 are each positioned at an angle with respect to a straight line running the length of the printing zone 120. This facilitates a measure of overlap at adjacent ends of the printhead chips 186 to ensure printing continuity.

It is clear from the above referenced United States applications and patents that a pagewidth printhead including printhead chips as described above can incorporate up to 84 000 nozzle arrangements. It follows that, by using the printhead chips 186, it is possible for the print assembly 14 to have over as many as 200 000 nozzle arrangements. It follows that over 200 000 dots can be printed on the paper 22 in the printing zone 120. In one particular example, the seventy-two printhead chips 186 provide a print width of 57.6 inches with 552 960 nozzle arrangements 210.

The nozzle arrangements 210 of each chip 186 are positioned side-by-side in two rows in a staggered fashion. It follows that true 1600 dpi printing can be achieved with the printhead chips 186.

Each printhead chip 186 therefore includes 7680 nozzle arrangements 210. Each nozzle arrangement 210 is independently controlled by the PCB 42 to eject a 1-picolitre drop on demand. The integrated circuit fabrication technology used is based on Very Large Scale Integration (VLSI) technology that is fully described in the above referenced applications and patents. As a result of the manufacturing techniques used, each nozzle arrangement 210 can be as little as 32 microns wide. This allows each printhead chip 186 to have a surface area as little as 21 mm<sup>2</sup>.

The characteristics of each nozzle arrangement 210 are such that it is capable of being driven at a cyclical rate of up to 80 kHz by its associated PEC 48. This permits printing of up to 21.6 billion drops per second that provides thirty-five thousand square feet per hour at 1600 dpi.

Each printhead chip 186 is connected to its associated PCB 42 with the flexible PCB 58. It follows that each flexible PCB 58 is connected to the CMOS layer 190 of its associated printhead chip 186.

Each PEC 48 is a page rendering engine application specific integrated circuit (ASIC) that receives input data relating to compressed page images from the printhead interface 176. The PEC 48 produces decompressed page images at up to six channels of bi-level dot data as output. It will be appreciated that each PEC 48 communicates with eight printhead chips 186 in this example. Each PEC 48 is capable, however, of communication with up to sixteen such printhead chips 186. In particular, each PEC 48 can address up to sixteen printhead chips in up to six color channels at 15 000 lines/sec. It follows that each PEC 48 allows for a 12.8-inch printhead width for full bleed printing of A3, A4 and letter pages.



Each PEC 48 is color space agnostic. This means that the PEC 48 can accept print data in any color. While each PEC 48 can accept contone data as CMYX or RGBX where X is an optional fourth channel, it can also accept contone data in any print color space. Additionally, each PEC 48 is configured to define a mechanism for arbitrary mapping of input channels to output channels. The PEC 48 is also configured for combining dots for ink optimization and the generation of channels based on any number of other channels. In this example, data input is typically based on CMYK for contone printing, K for a bi-level input, fixative, and optional further ink. The PEC 48 is also configured to generate a fixative channel for fast printing applications.

10 Each PEC 48 is configured to be resolution agnostic. This means that each PEC 48 simply provides a mapping between input resolutions and output resolutions by means of various scale factors. In this example, the expected output resolution is 1600 dpi. However, the PEC 48 does not store any data to this effect.

Each PEC 48 is also configured to be page-length agnostic. Each PEC 48 operates a printing band at a time and a page can have any number of bands. It follows that a "page" can have any reasonable length.

Each PEC 48 defines an interface so that it can be synchronized with other PEC's 48, as is the requirement with this invention. This allows a simple two-PEC solution for simultaneous A3/A4/Letter duplex printing. This also allows each PEC 48 to be responsible  
20 for the printing of only a portion of a page. It will be appreciated that combining synchronization functionality with partial page rendering allows multiple PEC's to be readily combined for alternative printing requirements including simultaneous duplex printing, wide format printing, commercial printing, specialist high contone resolution printing, and printing applications where more than six ink channels are required.

The following table sets out the features of each PEC 48 and its associated benefits.

**Table 1. Features and Benefits of PEC**

Feature	Benefits
Optimized print architecture in hardware	30ppm full page photographic quality color printing from a desktop PC
0.18micron CMOS ( >3 million transistors )	High speed Low cost High functionality
1.8 billion dots per second	Extremely fast page generation
15,000 lines per second at 1600 dpi	1.1 A4/Letter pages per PEC chip per second

1 chip drives up to 122,880 nozzles	Low cost page-width printers
1 chip drives up to 6 color planes	99% of printers can use 1 chip per page
Sophisticated internal memory buffering and caching	Only requires 1 external memory, leading to low cost systems
JPEG expansion	low bandwidth from PC low memory requirements in printer
Lossless bitplane expansion	high resolution text and line art with low bandwidth from PC (e.g. over USB)
Netpage tag expansion	Generates interactive paper
Stochastic dispersed dot dither	Optically smooth image quality No moire effects
Hardware compositor for 6 image planes	Pages composited in real-time
Dead nozzle compensation	Extends printhead life and yield Reduces printhead cost
Color space agnostic	Compatible with all inksets and image sources including RGB, CMYK, spot, CIE L*a*b*, hexachrome, YCrCbK, sRGB and other
Color space conversion	Higher quality / lower bandwidth
Computer interface agnostic	Works with USB1, USB2, IEEE1394 (Firewire), ethernet, IEEE1284 (Centronics)
Variable page length	Print any page length (up to 64 km)
Cascadable in resolution	Printers of any resolution
Cascadable in color depth	Special color sets e.g. hexachrome can be used
Cascadable in image size	Printers of any width
Cascadable in pages	Printers can print both sides simultaneously
Cascadable in speed	Very high speed printers can be built
Fixative channel data generation	Extremely fast ink drying without wastage
Built-in security	Revenue models are protected
Undercolor removal on dot-by-dot basis	Reduced ink usage
Does not require fonts for high speed operation	No font substitution or missing fonts
Flexible printhead configuration	Many configurations of printheads are supported by one chip type
Drives Memjet™ printheads directly	No print driver chips required, results in lower cost
Determines dot accurate ink usage	Removes need for physical ink monitoring system in ink cartridges

In Figure 10, there is shown a block diagram of the PEC 48. The PEC 48 includes a micro controller interface in the form of a high-speed interface 214 through which an

external micro controller 216 can write to the 64 Mbit DRAM chip 50. The high-speed interface 214 forms part of a data input means of the PEC 48.

The PEC 48 also includes a control circuitry interface in the form of a low speed serial interface 220 through which the micro controller 216 can access registers of the PEC 48 and the DRAM chip 50.

The PEC 48 also includes page expansion circuitry in the form of a page expansion unit (PEU) 222 that receives data relating to compressed pages and renders it into data relating to bi-level dots. Line loader and line formatter circuitry in the form of a line loader/formatter unit 224 is also provided that formats dots for a given print line destined for a printhead interface 226 that communicates directly with the printhead chips 186 of each printhead module 46.

As can be seen, the PEC 48 performs three basic tasks. These are:

- a) Accepting register and DRAM access commands via the low speed interface 220 (or from the external DRAM chip 50).
- b) Accepting DRAM write accesses (typically compressed page bands and register command blocks) via the high speed interface 214.
- c) Rendering page bands from the external DRAM chip 50 to the printhead chips 186.

These tasks are independent. However, they do share the external DRAM chip 50. It follows that arbitration is required. The PEC 48 is configured so that DRAM accesses required for rendering page bands always have the highest priority.

The PEC 48 includes control circuitry in the form of a PEC controller 228 that provides external clients with the means to read and write PEC registers, and read and write DRAM in single 32 bit data chunks.

The DRAM chip 50 is connected to memory storage control circuitry in the form of an SDRAM controller 234. In turn, the SDRAM controller 234 is connected to memory storage control circuitry in the form of a DRAM interface unit 236.

The PEC 48 includes a data bus 230 and a low speed serial bus 232. Both the SDRAM controller 234 and the DRAM interface unit 236 are connected to the low speed serial bus 232. The PEC controller 228 is connected to the data bus 230. The PEC controller 228 is also connected to the low speed serial bus 232 via the low speed interface 220. The high-speed interface 214, the PEU 222 and the line loader/formatter unit are also connected to the data bus 230.

In use, since the PEC 48 prints page bands from DRAM, a given band B is loaded into DRAM via the high-speed interface 214 before printing can begin. Then, while the PEC 48 is rendering band B via the PEU, band B+1 can be loaded to DRAM. While band B+1 is being expanded and printed, band B+2 can be loaded, and so on.

In the following table, the various components of the PEC 48 mentioned above are described briefly.

**Table 2. Units within PEC (high level)**

unit acronym	unit name	reference numeral	description
DIU	DRAM interface unit	236	Provides the interface for DRAM read and write access for the various PEC units. The DIU provides arbitration between competing units and passes on DRAM requests to the SCU.
HSI	High speed interface	214	Provides external clients (such as the microcontroller) with the means to write to DRAM.
LLFU	Line loader formatter unit	224	Reads the expanded page image from line store, formatting the data appropriately for the Memjet printhead.
LSI	Low speed interface	220	Provides external clients with the means to send commands to the PCU and receive register reads.
PCU	PEC controller	228	Provides external clients with the means to read and write PEC registers, and read and write DRAM in single 32-bit chunks.
PEU	Page expansion unit	222	Reads compressed page data and writes out the decompressed form of the same to DRAM.
PHI	Printhead interface	226	Is responsible for sending dot data to the Memjet printhead segments and for providing line synchronization between multiple PECs.
SCU	SDRAM controller unit	234	Provides the DIU with access to the external DRAM.

- 10 An expanded block diagram of the PEU 222 is shown in Figure 11. In the following table, the various components of the PEU 222 are described briefly.

**Table 3. Units within Page Expansion Unit (high level)**

unit acronym	unit name	reference numeral	description
CDU	Contone decoder unit	238	Expands JPEG compressed contone layer and writes decompressed

			contone to DRAM
CLBI	Contone line buffer interface	240	Provides line buffering between CRU and HCU
CRU	Contone reader unit	242	Reads expanded contone image from DRAM
DNC	Dead nozzle compensator	244	Compensates for dead nozzles by error diffusing dead nozzle data into surrounding dots.
DWU	Dotline writer unit	246	Writes out the 6 channels of dot data for a given printline to the line store DRAM
HCU	Half-toner compositor unit	248	Dithers contone layer and composites the bi-level spot 0 and position tag dots.
LBD	Lossless bilevel decoder	250	Expands compressed bi-level layer.
SLBI	Spot line buffer interface	252	Provides line buffering between LBD and HCU
TE	Tag encoder	254	Encodes tag data into line of tag dots.
TLBI	Tag line buffer interface	256	Provides line buffering between TE and HCU

A first stage in page expansion occurs along a pipeline defined by the CDU 238/CRU 242, the LBD 250 and the TE 254. The CDU 238 expands a JPEG-compressed contone (typically CMYK) layer. The LBD 250 expands a compressed bi-level layer (typically K), and the TE 254 encodes data tags for rendering (typically in infra-red ink) at a later stage. The CLBI 240, the SLBI 252 and the TLBI 256 receive output data from this stage.

The HCU 248 carries out a second stage. The HCU 248 dithers a contone layer and composites position tags and a bi-level spot0 layer over a resulting bi-level dithered layer.

- 10 A data stream generated by the HCU 248 is adjusted to create smooth transitions across overlapping segments or printhead chips 186. The HCU 248 is configured so that a number of options exist for the way in which compositing occurs. This stage can produce up to six channels of bi-level data. It should be noted that not all six channels might be present on the printhead chips 186. For example, the printhead chips 186 may be CMY only, with K pushed into the CMY channels and IR ignored. Alternatively, the position tags mentioned above may be printed in K if IR ink is not available or for testing purposes.

The DNC 244 carries out a third stage. In this stage, the DNC 244 compensates for dead nozzles in the printhead chips 186 by error diffusing dead nozzle data into surrounding dots.

Bi-level, six channel dot-data (typically CMYK-IRF) generated in the above stages is buffered and written out to a set of line buffers stored in the off-chip DRAM via the DWU 246.

In a final stage, the dot-data is loaded back from the DRAM, formatted for the printhead, and passed to the printhead interface 226 via a dot FIFO (not shown). The dot FIFO accepts data from the line loader/formatter unit 224 at pclk rate, while the printhead interface 226 removes data from the FIFO and sends it to the printhead chips 186 at a rate of either pclk/4, pclk/2 or pclk.

Figure 12 simply shows the PEC 48 incorporating the exploded PEU 222.

The printing benefits associated with the printhead chips 186 are set out in detail in the above referenced applications and patents. However, some benefits are particularly important when applied to wide printing formats.

A particular benefit is the high number of nozzle arrangements 210 per printhead chip 186. This facilitates extremely rapid printing in that a single print cycle can achieve an image band. It follows that it is not necessary for further print cycles to be used to fill in "missing" dots as is the case with a scanning printhead.

The PEC's 48 provide the necessary synchronized control of the printhead chips 186 as described above. Furthermore, as is clear from a number of the above referenced applications and patents, for example 09/113,053, the printhead chips 186 allow for the conversion from analogue printing processes to fully digital processes. This allows for a substantial amount of flexibility and speed. Digital control of the printhead chips 186 is by means of the PEC's 48. The fact that the PEC's 48 digitally control the printhead chips 186 allows for the high printing speed of up to 21.6 billion drops per second. In particular, the need for separate printhead chip drivers is removed, which is key to the high printing speed of the chips 186.

The incorporation of the CMOS layer 190 serves to integrate CMOS technology with MEMS technology on each printhead chip 186. It follows that at least one off-chip connection for each nozzle arrangement 210 is not required. It will be appreciated that such a requirement would make a printhead unreliable and cost-prohibitive to manufacture.

A further important advantage associated with the printer 10 is that a width of the printing zone 120 is extremely small when compared to the length. In a particular example, the printing zone 120 can be as little as 0.5 mm thick. It will be appreciated that it is necessary to achieve extremely stable paper movement through the printing zone 120 in order to ensure that accurate printing takes place in the printing zone. The narrow width of the printing zone 120 facilitates minimal control over the paper 22 as it passes through the printing zone.

10 In the event that a substantially wider printing zone were provided, it would be necessary to provide further control over movement of the paper 22 through such a printing zone. This would require such devices as vacuum platens to retain the paper 22 against any form of pivotal or lateral movement as the paper 22 moves through the printing zone. This could greatly increase the cost of the wide format printer.

20 This highlights some reasons why thermal or bubble jet and piezoelectric printheads would not be practical choices when attempting to achieve the printing characteristics of the printer 10. As set out in the above referenced applications and patents, such printheads are not suitable for providing the high density of nozzle arrangements achieved with the printheads of the above referenced matters. It follows that, in attempting to apply thermal and piezoelectric printheads to a wide format printer, it would be necessary to have a relatively wide printing zone so that overlapping of printheads could occur to the necessary extent. This would immediately raise the problem mentioned above. Still further, especially with the thermal printheads, a suitable cooling system would be required to keep the temperature in the printing zone at a reasonable level. This would also increase the cost to an unacceptably high level.

In order to achieve an appreciation of the speed of the printer 10 at a resolution of 1600 dpi, the following comparative table is set out below. It should be noted that the purpose of the following table is simply to illustrate the speed of printing and is not intended to denigrate the various printers used for comparison.

## Wide Format Printers

<b>Menjet</b>	OEM Printhead Print Width (inches)				38.4	44.8	51.2	57.6	64.0	70.4	76.8
	Number of Printhead Chips				48	56	64	72	80	88	96
	Number of Nozzles				368,640	430,080	491,520	552,960	614,400	675,840	737,280
	Max. print speed (sq ft/hr at 1600 x 1600 dpi)				17,578	20,508	23,438	26,367	29,297	32,227	35,156
<b>Comparison</b>	<b>Make</b>	<b>Model</b>	<b>Resolution</b>	<b>Speed</b>	<b>Speed Advantage (# of times faster)</b>						
	HP	1000 / 5000	600 x 600	120	146	171	195	220	244	269	293
	HP	3000 / 3500	600 x 300	72	244	285	326	366	407	448	488
	Epson	7000 / 10000	720 x 720	90	195	228	260	293	326	358	391
	Encad	Novajet 800	600 x 600	96	183	214	244	275	305	336	366
	Gretag	Arizona	Draft mode	444	40	46	53	59	66	73	79
	Gretag	Arizona	309 x 618	220	80	93	107	120	133	146	160
	Colorspan	Mach X11	600 x 600	115	153	178	204	229	255	280	306
	Canon	BJW 9000	600 x 1200	72	244	285	326	366	407	448	488
	Mutoh	Albatross	792 x 792	65	270	316	361	406	451	496	541
	Roland	HiFi Jet	720 x 720	96	183	214	244	275	305	336	366
	Nur	Fresco	360 x 360	300	59	68	78	88	98	107	117

As is known by those of skill in the fabrication of integrated circuits, while a set up cost for the manufacture of an integrated circuit device can be high, the cost of commercial manufacture of such devices is relatively low. It follows that Applicant envisages that the cost of manufacture of a wide format printer in accordance with this invention will be comparable to the cost of manufacture of the wide format printers listed in the above table.

10 It will be apparent to those skilled in the art that many obvious modifications and variations may be made to the embodiments described herein without departing from the spirit or scope of the invention.



**WE CLAIM**

1. A method of processing an image for printing, the method comprising the steps of:  
receiving image data in an image storage format;  
transforming the image data into print data at a rate of at least one billion pixels per second; and  
communicating the print data to a printhead.
2. A method as claimed in claim 1, which includes the step of transforming the image  
10 data into print data at a rate of at least ten billion pixels per second.
3. A method as claimed in claim 2, which includes the step of transforming the image  
data into print data at a rate of at least twenty billion pixels per second.
4. A method as claimed in claim 3, which includes the step of communicating the print  
data to the printhead at a rate of at least twenty billion pixels per second.
5. A method as claimed in claim 1, which includes the step of receiving the image data  
20 in a compressed format with the step of transforming the image data including the step of  
expanding the image data to produce output data representing decompressed page images.
6. A method as claimed in claim 5, which includes the step of expanding the image  
data to produce output data representing six color channels in a bi-level format.
7. A method as claimed in claim 1, in which the step of communicating the print data  
to a printhead includes the step of addressing a number of printhead chips of the printhead  
with the print data.
8. An image processing apparatus for a printer, the image processing apparatus  
30 comprising  
a data input means that is configured to receive image data in an image storage  
format;

a data processing means that is operatively connected to the data input means and is configured to process the image data at a rate of at least one billion pixels per second to transform the data into print data; and

a data communication means that is operatively connected to the data processing means and is configured to communicate the print data to a printhead.

9. An image processing apparatus as claimed in claim 8, which includes at least one print engine controller, the data input means, the data processing means, and the data communication means being at least partly defined by the print engine controller.

10

10. An image processing apparatus as claimed in claim 9, which includes at least one memory storage device, the, or each, memory storage device being connected to one respective print engine controller to facilitate the temporary storage of the image and print data while the image and print data is processed and communicated to the printhead.

11. An image processing apparatus as claimed in claim 10, which includes at least one micro controller that is connected to one respective print engine controller via a micro controller interface to control operation of the print engine controller, the data input means including the micro controller interface.

20

12. An image processing apparatus as claimed in claim 11, which includes a number of print engine controllers, a number of corresponding memory storage devices and a number of micro controllers, each print engine controller, each memory storage device and each micro controller being operatively connectable to a set of printhead chips, the printhead being defined by a number of the sets of printhead chips.

13. An image processing apparatus as claimed in claim 12, in which each print engine controller is in the form of an application specific integrated circuit (ASIC) that includes a data bus to facilitate communication between various components of the print engine controller.

30

14. An image processing apparatus as claimed in claim 13, in which each print engine controller includes memory storage control circuitry and memory storage interface circuitry

operatively connected between its associated memory storage device and the data bus, the memory storage interface circuitry being configured to provide an interface for read and write access to the memory storage device for the various components of the print engine controller and to provide arbitration between competing components for read and write access to the memory storage device, and the memory storage control circuitry being configured to provide the memory storage interface circuitry with access to the memory storage device.

10 15. An image processing apparatus as claimed in claim 14, in which each print engine controller includes control circuitry and a control circuitry interface, the control circuitry being operatively connected between the data bus and the control circuitry interface, the control circuitry being configured to provide a means for reading and writing registers of the print engine controller and for reading and writing to the memory storage device in data blocks having a predetermined bit size and the control circuitry interface being configured to receive register reads to be written by the control circuitry.

16. An image processing apparatus as claimed in claim 15, in which each print engine controller includes page expansion circuitry that is operatively connected to the data bus and is configured to read compressed image data and to write out decompressed image data

20 17. An image processing apparatus as claimed in claim 16, in which each print engine controller includes line loading and line formatting circuitry and printhead interface circuitry, the line loading and line formatting circuitry being connected between the data bus and the printhead interface circuitry that is operatively connected to the associated printhead chips, the line loading and line formatting circuitry being configured to read the decompressed image data, to format the decompressed image data for the printhead chips and to write the formatted decompressed image data to the printhead interface and the printhead interface circuitry being configured for sending dot data to the printhead chips and for providing suitable synchronization between a number of the print engine

30 controllers.

18. An inkjet printer that comprises  
a support structure;

a platen positioned in the support structure;  
a print assembly positioned operatively with respect to the platen to define a printing zone between the platen and the print assembly, the print assembly comprising  
an elongate carrier; and  
a number of printhead chips positioned on the carrier, the printhead chips together defining a printhead;  
an image processing apparatus that is operatively arranged with respect to the print assembly, the image processing apparatus comprising  
a data input means configured to receive image data in an image storage  
10 format;  
a data processing means that is configured to process the image data at a rate of at least one billion pixels per second to transform the data into print data; and  
a data communication means that is configured to communicate the print data to the printhead; and  
a feed mechanism positioned on the support structure for feeding a print medium through the printing zone.

**ABSTRACT**

An image processing apparatus for a printer includes a print engine controller that is configured to receive image data in an image storage format. The print engine controller includes data processing circuitry that is configured to process the image data at a rate of at least one billion pixels per second to transform the data into print data. The print engine controller includes data communication circuitry that is operatively connected to the data processing circuitry and is configured to communicate the print data to a printhead.

2025 RELEASE UNDER E.O. 14176

Please type a plus sign (+) inside this box → ☐

PTO/SB/01 (12-97)  
Approved for use through 9/30/00. OMB 0651-0032  
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

**DECLARATION FOR UTILITY OR  
DESIGN  
PATENT APPLICATION  
(37 CFR 1.63)**

☒ Declaration Submitted with Initial Filing **OR** ☐ Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

Attorney Docket Number YU183US

First Named Inventor KIA SILVERBROOK

**COMPLETE IF KNOWN**

Application Number /

Filing Date

Group Art Unit

Examiner Name

As a below named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**The Processing of Images for High Volume Pagewidth Printing**

the specification of which (Title of the Invention)

☒ is attached hereto  
OR

☐ was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application Number and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?	
				YES	NO
PO2592	Australia	03/25/98	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
PO7991	Australia	07/15/97	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Certified copies are not submitted as this is a CIP of USSN 09/112,767 filed on July 10, 1998			<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

☐ Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

Application Number(s)	Filing Date (MM/DD/YYYY)	<input type="checkbox"/> Additional provisional application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

[Page 1 of 2]

Burden Hour Statement: This form is estimated to take 0.4 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

Please type a plus sign (+) inside this box → ☐PTO/SB/01 (12-97)  
Approved for use through 9/30/00. OMB 0651-0032Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE  
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.**DECLARATION — Utility or Design Patent Application**

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer  
Number Bar Code  
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☒ Customer Number or Bar Code Label **24011** OR ☐ Correspondence address below

Name	Kia Silverbrook				
Address	Silverbrook Research Pty Ltd				
Address	393 Darling Street				
City	Balmain	State	NSW	ZIP	2041
Country	Australia	Telephone	61-2-9818-6633	Fax	61-2-9818-6711

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.


Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname	
KIA		SILVERBROOK	
Inventor's Signature	Date		April 8, 2002
Residence: City	Balmain	State	NSW
		Country	Australia
Post Office Address	393 Darling Street		
Post Office Address			
City	Balmain	State	NSW
		ZIP	2041
		Country	Australia

☐ Additional inventors are being named on the supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

United States Patent & Trademark Office  
Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

☐ Page(s) \_\_\_\_\_ of \_\_\_\_\_ were not present  
for scanning. (Document title)

*There are only 2 Pages on declaration  
& not on 3 Pages.*

☐ *Scanned copy is best available.*



FIG. 1




FIG. 1




FIG. 2

FIG. 3




FIG. 3

FIG. 4 - perspective view




FIG. 4




FIG. 5




FIG. 6




FIG. 7

FIG. 8




FIG. 8






FIG. 9



CONTROLLER




FIG. 11

2025-05-06 10:10:10





FIG. 12






FIG. 14

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☒ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.